

■ ステンレス溶接鋼管重量表

(単位 : kg/4m)

B	A	肉厚 (mm)		1.2	1.5	2.0	2.5	3.0	3.5	4.0	5.0	5.5	6.0	6.5
		外径 (mm)												
1/8	6	10.5	1.11	1.34	1.69	1.99								
			1.12	1.35	1.70	2.00								
		12.7	1.38	1.67	2.13									
			1.38	1.68	2.14									
1/4	8	13.8	1.51	1.84	2.35	2.82	3.23							
			1.52	1.85	2.37	2.83	3.25							
		16.0	1.77	2.17	2.79									
			1.78	2.18	2.81									
3/8	10	17.3	1.92	2.36	3.05	3.69	4.28							
			1.94	2.38	3.07	3.71	4.32							
		19.0	2.13	2.62	3.39									
			2.14	2.63	3.41									
1/2	15	21.7	2.45	3.02	3.92	4.80	5.60							
			2.47	3.04	3.95	4.80	5.64							
		25.4	2.89	3.57	4.68	5.72	6.68							
			2.91	3.60	4.68	5.76	6.72							
3/4	20	27.2	3.11	3.84	5.04	6.16	7.24							
			3.13	3.86	5.04	6.20	7.28							
		32.0	3.68	4.56	5.96	7.36	8.68							
			3.71	4.60	6.00	7.40	8.72							
1	25	34.0	3.92	4.84	6.36	7.84	9.28	10.6	12.0					
			3.95	4.88	6.40	7.88	9.32	10.7	12.0					
		38.0	4.40	5.44	7.16	8.84	10.5	12.0	13.6					
			4.44	5.48	7.24	8.88	10.5	12.1	13.6					
1 1/4	32	42.7	4.96	6.16	8.12	10.0	11.9	13.7	15.4					
			5.00	6.20	8.16	10.1	12.0	13.8	15.5					
1 1/2	40	48.6	5.68	7.04	9.28	11.5	13.6	15.7	17.8					
			5.72	7.08	9.36	11.5	13.7	15.8	17.9					
		50.8	5.92	7.36	9.72	12.0	14.3	16.5	18.6					
			5.96	7.40	9.80	12.1	14.4	16.6	18.8					
2	50	60.5		8.80	11.6	14.4	17.2	19.9	22.5	27.6	30.2			
				8.88	11.7	14.6	17.3	20.0	22.7	27.8	30.3			
		63.5		9.28	12.2	15.2	18.1	20.9	23.7					
				9.32	12.3	15.3	18.2	21.0	23.9					
2 1/2	65	76.3		11.2	14.8	18.4	21.9	25.4	28.8	35.5	38.8	42.0		
				11.2	14.9	18.5	22.0	25.6	29.0	35.8	39.0	42.4		
3	80	89.1		13.1	17.4	21.6	25.7	29.8	33.9	42.0	46.0	49.6		
				13.2	17.5	21.7	25.9	30.0	34.1	42.0	46.0	50.0		
3 1/2	90	101.6			19.8	24.7	29.5	34.2	38.9	48.0			57.2	
					20.0	24.8	29.7	34.4	39.2	48.4			57.6	
4	100	114.3			22.4	27.8	33.3	38.6	44.0	54.4			64.8	
					22.5	28.0	33.5	38.9	44.4	54.8			65.2	
5	125	139.8			27.5	34.2	40.8	47.6	54.0	67.2			80.0	86.4
					27.6	34.4	41.2	48.0	54.4	67.6			80.4	86.8
6	150	165.2			32.5	40.4	48.4	56.4	64.4	80.0			95.2	103
					32.7	40.8	48.8	56.8	64.8	80.4			95.6	104
8	200	216.3					63.6		84.8	105			126	136
							64.0		85.2	106			126	137
10	250	267.4					79.2	92.0	105	131			156	169
							79.6	92.8	106	132			157	170
12	300	318.5					94.4		125	156			187	202
							94.8		126	157			188	203
14	350	355.6							140	175			209	226
									141	176			210	228
16	400	406.4							160	200			239	259
									162	201			241	261
18	450	457.2							181	225			270	292
									182	227			272	294
20	500	508.0							201	250	275	300	325	
									202	252	277	302	327	
22	550	558.8							221	276	303	330	358	
									222	278	305	333	360	
24	600	609.6							241	301	331	361	391	
									243	303	333	363	393	

 上段 SUS304、304L
 下段 SUS316、316L